

Standard Gasurveyor 500 Instruments

The standard 4 button Gasurveyor 500 Range detects a combination of Flammable and Toxic gases common in many application, performing as both a Combustible gas Indicator and Confined Space Monitor, and providing automatic and manual datalogging as standard.

| Instrument | Gases Detected |
|----------------|-----------------------------|
| Gasurveyor 511 | LEL & Volume |
| Gasurveyor 512 | PPM, LEL & Vol. |
| Gasurveyor 521 | LEL & Vol. O2 |
| Gasurveyor 522 | PPM, LEL & Vol. O2 |
| Gasurveyor 523 | LEL & Vol. H2S |
| Gasurveyor 524 | PPM, LEL & Vol. H2S |
| Gasurveyor 525 | LEL & Vol. CO |
| Gasurveyor 526 | PPM, LEL & Vol. CO |
| Gasurveyor 531 | LEL & Vol. O2, CO |
| Gasurveyor 532 | PPM, LEL & Vol. O2, H2S |
| Gasurveyor 533 | LEL & Vol. O2, CO |
| Gasurveyor 534 | PPM, LEL & Vol. O2, CO |
| Gasurveyor 536 | PPM, LEL & Vol. H2S, CO |
| Gasurveyor 541 | LEL & Vol. O2, H2S, CO |
| Gasurveyor 542 | PPM, LEL & Vol. O2, H2S, CO |