





SamplerPak Specifications

Size	7.4 x 1.3 x 2.1 in. / 18.8 x 3.35 x 5.4 cm
Weight	6.2 oz. / 175 g
Temperature	-4 to +122°F / -20 to +50°C (North American model) -4 to +104°F / -20 to +40°C (European model)
Humidity	5% - 95% RH (non-condensing)
Alarms	- Visual and audible (90dB) - Warning conditions: Low flow, low battery, system fault
Sample flow rate	300 ml/min (typical)
Sample distance	50 ft. / 15.2 m
Sample delay time	3 seconds per 1 ft. / 0.3 m
Outlet connection	1/8 in. / 0.32 cm barbed fitting for flexible sampling hose
Inlet connection	Flexible sampling hose: 1/8 in. / 0.32 cm Rigid sample tube: 1/4 in. / 0.63 cm O.D.
Typical battery life	30 hrs with 2 AA alkaline batteries or 2 AA NiMH rechargeable batteries
Ratings	EMI/RFI: Complies with EMC Directive 89/336/EEC
Certifications and approvals	 Class I, Div. 1, Gr. A, B, C, D  American Bureau of Shipping ATEX:  0539  II 2 G T4* EEx ia IIC T4* IECEx: Ex ia IIC T4* CE: European Conformity <i>*Temperature codes may vary as a function of the batteries installed. Please see owner's manual for a complete listing of compatible batteries and codes.</i>
Warranty	Full 2 year warranty